

# WALL MOUNT FLANGE DISCONNECT ENCLOSURE STAINLESS STEEL TYPE 4X

## CONSTRUCTION DETAILS

- ) 14 gauge Type 304 or 316 stainless steel
- ) Seams continuously welded and ground smooth
- ) External welded on mounting brackets
- ) Stainless steel screw style door clamps on three sides to secure the door
- ) Padlock feature on door
- ) Continuous hinge with removable stainless steel hinge pin
- ) Collar studs for mounting optional rear sub panel
- ) Interlock bracket for attaching disconnect door catch
- ) Bonding stud on door
- ) Print pocket on door
- ) Closed cell oil resistant neoprene gasket

*\*Custom is what we do. Contact our sales office for a quote on custom enclosure features.*

## FINISH

- ) Door and all sides to have #4 brushed finish
  - ) Optional sub panel painted RAL 9003 white<sup>2</sup>
- <sup>1</sup> Finish with a standard RAL powder color inside and out of your choice at no additional cost  
<sup>2</sup> Galvanized sub panel available; mill finish

## INDUSTRY STANDARDS

- ) Nema Type 4X, 4, 12, 13, and 3R
- ) UL Listed Type 4X, 4, 12, 13, and 3R
- ) CSA Type 4X, 4, and 12
- ) IEC60529 IP66

## ADDITIONAL AVAILABLE MODELS

- ) Single Door With Three Point Handle

IEC FILE REFERENCE: N4X\_SS\_1D\_WM\_FMD

